



Climax Lubricants & Equipment Co.

CLIMAX SPEC SHEET - #1034 LUBRICANT/SEALANT

DROPPING POINT.....	NON -DROPPING
BASE OIL.....	SYNTHETIC-POLYESTER
SHELF LIFE.....	5-YEARS (CONTROLLED ENVIROMENT)
OXIDATION STABILITY.....	EXCELLENT
TEMPERATURE RANGE.....	-40 DEG.F.TO +400 DEG.F.
PENETRATION (BULK).....	NLGI GRADE #3 (ASTM D-217= 220-250)
(STICK).....	NLGI GRADE #6 (ASTM D-217= 85-115)
THICKENER.....	INORGANIC
COLOR.....	MAROON

NON TOXIC-HAZARDOUS MATERIAL
FLASH POINT ABOVE 400 DEG.F.
NON FLAMMABLE
Manufactured / Country of Origin – U.S.A.

In addition to a general purpose sealant for liquid and gaseous aliphatic hydrocarbon service; (for example: wet or dry natural gas), this sealant has excellent resistance to internal combustion fuels: regular, premium and high octane gasolines- including oxygenated and reformulated fuels, jet fuels, aviation gasoline, kerosene, fuel blending ingredients; such as alkylate and platformate, fuel and lubricating oils, mixtures of these products and water in all proportions.

Stephen D. Frauenberger, President - Sales/Manufacturing
E-mail: sales@climaxlube.com
Climax Lubricants & Equipment Co. – U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012
713-923-2626 – Fax 713-928-9025 - climaxlube@aol.com**