



Climax Lubricants & Equipment Co.

CLIMAX SPEC SHEET ~ 1034 PAC-EZ (VALVE STEM PACKING)

DROPPING POINT.....	NON -DROPPING
BASE OIL.....	SYNTHETIC-POLYESTER
SHELF LIFE.....	5-YEARS (Controlled Environment)
OXIDATION STABILITY.....	EXCELLENT
TEMPERATURE RANGE.....	-40 DEG.F.TO +500 DEG.F.
PENETRATION.....	N/A
THICKENER.....	INORGANIC RHEOLOGICAL ADDITIVE
FILLER.....	TEFLON, CEDAR FIBER, MILLED FIBER
COLOR.....	GREEN

NON TOXIC-HAZARDOUS MATERIAL
FLASH POINT ABOVE 400 DEG.F.
NON FLAMMABLE
Manufactured/Country of Origin – U.S.A.

Climax 1034 Pac-Ez is used for API Gate Valve Stems, Rockwell Hyperseals, Orbit Ball Valves, Etc. In addition to a general purpose packing for liquid and gaseous aliphatic hydrocarbon service; (for example: wet or dry natural gas), this packing has excellent resistance to internal combustion fuels: regular, premium and high octane gasolines- including oxygenated and reformulated fuels, jet fuels, aviation gasoline, kerosene, fuel blending ingredients; such as alkylate and platform ate, fuel and lubricating oils, mixtures of these products and water in all proportions.

Stephen D. Frauenberger, President - Sales/Manufacturing
E-Mail: sales@climaxlube.com
Climax Lubricants & Equipment Company - U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012
713-923-2626 – Fax 713-928-9025 - climaxlube@aol.com**