



Climax Lubricants & Equipment Co.

CLIMAX SPEC SHEET ~ #104 STICK LUBRICANT/SEALANT

DROPPING POINT.....	NON -DROPPING
BASE OIL.....	SYNTHETIC
SHELF LIFE.....	5 YEARS (CONTROLLED ENVIROMENT)
OXIDATION STABILITY.....	GOOD
TEMPERATURE RANGE.....	0 DEG.F.TO +500 DEG.F.
PENETRATION.....	NLGI GRADE #6 (ASTM 85-115)
THICKENER.....	INORGANIC
FILLER.....	TEFLON*
COLOR.....	BLUE

NON TOXIC-HAZARDOUS MATERIAL

FLASH POINT ABOVE 400 DEG.F.

NON FLAMMABLE

*DUPONT TRADEMARK

Manufactured/Country of Origin – U.S.A.

An all purpose High Temperature Hydrocarbon and Natural Gas lubricant that is specifically designed for badly worn-scored Plug Valves or Ball Valves. This material is suitable for Natural Gas Pipelines, Refineries, Gasoline and Petrochemical Plants - L.P.G`s, kerosene, fuel oils, crude distillates, casing head gas, mineral oils, greases, light naphthas,ect. Unsuitable for aromatic solvents, strong acids and alkalies.

Stephen D. Frauenberger, President - Sales/Manufacturing

Email: sales@climaxlube.com

Climax Lubricants & Equipment Co. – U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012
713-923-2626 – Fax 713-928-9025 - climaxlube@aol.com**