



Climax Lubricants & Equipment Co.

CLIMAX SPEC SHEET ~ 109 PAC-EZ ~ VALVE STEM PACKING

DROPPING POINT.....	NON -DROPPING
BASE OIL.....	SYNTHETIC
SHELF LIFE.....	INDEFINITE
OXIDATION STABILITY.....	GOOD
TEMPERATURE RANGE.....	-40 DEG.F.TO +500 DEG.F.
PENETRATION.....	N/A
THICKENER.....	INORGANIC HYDRATED-SILICATE
FILLER.....	TEFLON
COLOR.....	MAROON

NON TOXIC-HAZARDOUS MATERIAL
FLASH POINT ABOVE 400 DEG.F.
NON FLAMMABLE
Manufactured/Country of Origin – U.S.A.

Climax 109 Pac-Ez is used for Liquid and Gaseous Aliphatic Hydrocarbons in API Gate Valve Stems, Rockwell Hyperseals, Orbit Ball Valves, Etc.

Recommended for these services: Refinery and Petrochemical blends, Aniline, Carbon Tetrachloride, Benzenes, Butadiene, Butane, Chloropentane, Cumenes, Ethane, Ethylene, M.T.B.E., Methane, Methylene Chloride, Naphthas, Hexane, Isobutane, Propane (Wet or Dry), Propylenes, Rubber Solvents, Styrene, Toluenes, Xylenes and other LPG'S.

Stephen D. Frauenberger, President – Sales/Manufacturing
Email: sales@climaxlube.com
Climax Lubricants & Equipment Co. – U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012
713-923-2626 – Fax 713-928-9025 - climaxlube@aol.com**