



## Climax Lubricants & Equipment Co.

### CLIMAX SPEC SHEET~ #110-S LUBRICANT/SEALANT

DROPPING POINT.....	NON-DROPPING
BASE OIL.....	SYNTHETIC
SHELF LIFE.....	5-YEARS (CONTROLLED ENVIROMENT)
OXIDATION STABILITY.....	GOOD
TEMPERATURE RANGE..... (NO-MELT= 300 DEG. F)	-20 DEG.F.TO +400 DEG.F.
PENETRATION (BULK).....	NLGI GRADE #3 (ASTM D-217 = 220-250)
THICKENER.....	INORGANIC
FILLER.....	HYDROUS-SILICATES
ADDITIVES.....	HYDROGEN SULFIDE SUPPRESSOR, OXIDATION CORROSION INHIBITOR
COLOR.....	YELLOW

NON TOXIC-HAZARDOUS MATERIAL  
FLASH POINT ABOVE 400 DEG.F.  
NON FLAMMABLE  
Manufactured/Country of Origin – U.S.A.

A special purpose medium temperature Hydrocarbon and Natural Gas lubricant-sealant for high pressure use in A.P.I. Gate valves and Wellhead Production. Designed for Sour gas and Sour Crude where H<sub>2</sub>S and CO<sub>2</sub> are present. Exhibits excellent corrosive protection. Also recommended for Natural Gas Pipelines, Refineries and Gasoline Plants.

Stephen D. Frauenberger, President – Sales/Manufacturing  
Email: [sales@climaxlube.com](mailto:sales@climaxlube.com)  
Climax Lubricants & Equipment Co. – U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012  
713-923-2626 – Fax 713-928-9025 - [climaxlube@aol.com](mailto:climaxlube@aol.com)**