



## Climax Lubricants & Equipment Co.

### CLIMAX SPEC SHEET- #204 LUBRICANT/SEALANT

DROPPING POINT.....	NON -DROPPING
BASE OIL.....	POLYDIMETHYL SILOXANE FLUID
SHELF LIFE.....	5 YEARS (CONTROLLED ENVIROMENT)
OXIDATION STABILITY.....	GOOD
TEMPERATURE RANGE.....	-50 DEG.F.TO +400 DEG.F.
PENETRATION.....	NLGI GRADE #3 (ASTM 220-250)
THICKENER.....	INORGANIC
COLOR.....	WHITE

NON TOXIC-HAZARDOUS MATERIAL  
FLASH POINT ABOVE 400 DEG.F.  
NON FLAMMABLE  
Manufactured / Country of Origin – U.S.A.

This silicone Lubricant/Sealant is recommended for Molten Sulphur, Vacuum services, Acetic Anhydride, Acetic Acid, High Concentrations of Sour Gas: CO-2 (Carbon dioxide) or H2S (Hydrogen Sulfide) in products. Also used for Hot Air or Water, Natural Gas, Chemical and Aqueous Solution Services. Food and Pharmaceutical applications as determined by user.

Stephen D. Frauenberger, President – Sales/Manufacturing  
E-Mail: [sales@climaxlube.com](mailto:sales@climaxlube.com)  
Climax Lubricants & Equipment Co. – U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012  
713-923-2626 – Fax 713-928-9025 - [climaxlube@aol.com](mailto:climaxlube@aol.com)**