



Climax Lubricants & Equipment Co.

CLIMAX SPEC SHEET ON #204 PAC-EZ

DROPPING POINT.....	NON-DROPPING
BASE OIL.....	POLYDIMETHYL SILOXANE FLUID
SHELF LIFE.....	INDEFINITE
OXIDATION STABILITY.....	GOOD
TEMPERATURE RANGE.....	-50 DEG.F.TO +400 DEG.F.
PENETRATION.....	N/A
THICKENER.....	INORGANIC
FILLER.....	*TEFLON, MILLED FIBER, KEVLAR
COLOR.....	YELLOW

NON TOXIC-HAZARDOUS MATERIAL
FLASH POINT ABOVE 400 DEG.F.
NON FLAMMABLE
*DuPont Trademark

This silicone packing is used for API Gate Valve stems and Rockwell Hyperseals ect. Pac-ez 204 is recommended for Molten Sulphur, Vacuum services, Acetic Anhydride, Acetic Acid, Ammonia(Gas or Liquid), High Concentrations of Sour Gas CO-2 (Carbon dioxide) or H2S (Hydrogen Sulfide) in products. Also used for Water, Natural Gas, Chemical and Aqueous Solution Services. Food and Pharmaceutical applications as determined by user.

Stephen D. Frauenberger, President – Sales/Manufacturing
Email: sales@climaxlube.com
Climax Lubricants & Equipment Company – U.S.A

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012
713-923-2626 – Fax 713-928-9025 - climaxlube@aol.com**