



## Climax Lubricants & Equipment Co.

### CLIMAX SPEC SHEET ~ #220 LUBRICANT/SEALANT

DROPPING POINT.....NON-DROPPING

BASE OIL.....SYNTHETIC-POLYESTER

SHELF LIFE.....5-YEARS  
(Controlled Environment)

OXIDATION STABILITY.....GOOD

TEMPERATURE RANGE.....-75 DEG.F.TO +250 DEG.F.

PENETRATION (BULK).....NLGI GRADE #3  
(ASTM D-217 = 220-250)

(STICK).....NLGI GRADE # 6  
(ASTM D-217 = 85-115)

THICKENER.....INORGANIC

COLOR.....TRANSLUCENT

NON TOXIC-HAZARDOUS MATERIAL  
FLASH POINT ABOVE 400 DEG.F.  
NON FLAMMABLE

A superior Hydrocarbon Lubricant-sealant that exhibits excellent Low Temperature capabilities. Climax 220 was developed for use in Alaska and other parts of the country where temperatures remain below -20 Deg. F. for sustained periods of time. Recommended for Liquid Services in Pipelines, Compressor stations, Gasoline plants, Crude Oil production and L.P.G.

Stephen D. Frauenberger, President – Sales/Manufacturing  
E-Mail: [sales@climaxlube.com](mailto:sales@climaxlube.com)  
Climax Lubricants & Equipment Co. – U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012  
713-923-2626 – Fax 713-928-9025 - [climaxlube@aol.com](mailto:climaxlube@aol.com)**