



Climax Lubricants & Equipment Co.

CLIMAX SPEC SHEET ~ #262 LUBRICANT/SEALANT

DROPPING POINT.....	NON -DROPPING
BASE OIL.....	SYNTHETIC-POLYESTER
SHELF LIFE.....	5-YEARS (CONTROLLED ENVIROMENT)
OXIDATION STABILITY.....	GOOD
TEMPERATURE RANGE.....	-85 DEG.F.TO +250 DEG.F.
PENETRATION (BULK).....	NLGI GRADE #3 (ASTM D-217 = 220-250)
(STICK).....	NLGI GRADE #6 (ASTM D-217 = 85-115)
THICKENER.....	INORGANIC
COLOR.....	TRANSLUCENT

NON TOXIC-HAZARDOUS MATERIAL
FLASH POINT ABOVE 400 DEG.F.
NON FLAMMABLE

A superior Hydrocarbon Lubricant-sealant that exhibits excellent Low Temperature capabilities.
Recommended for Gas Services in Pipelines and Compressor Stations.

Stephen D. Frauenberger, President-Sales/Manufacturing
E-Mail: sales@climaxlube.com
Climax Lubricants & Equipment Co. – U.S.A.

P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012
713-923-2626 – Fax 713-928-9025 - climaxlube@aol.com