



## Climax Lubricants & Equipment Co.

### CLIMAX SPEC SHEET ~ #333 PAC-EZ

DROPPING POINT.....	NON-DROPPING
BASE OIL.....	SYNTHETIC-POLYMERIZED HYDROCARBON DERIVATIVE
SHELF LIFE.....	5-YEARS
OXIDATION STABILITY.....	GOOD
TEMPERATURE RANGE.....	32 DEG.F.TO +750 DEG.F.
PENETRATION.....	N/A
THICKENER.....	METALLIC-SOAP
FILLER.....	GRAPHITE-KEVLAR
COLOR.....	BLACK

NON TOXIC-HAZARDOUS MATERIAL  
FLASH POINT ABOVE 400 DEG.F.  
NON FLAMMABLE

A specially designed graphite-kevlar impregnated Packing for Hi-Pressure and Hi-Temp steam expansion joints. Also recommended as a valve stem packing for temperatures exceeding 500 DEG.F. Principle services include hot aliphatic hydrocarbon liquids, gases and vapors.

Stephen D. Frauenberger, President – Sales/Manufacturing  
E-MAIL: [sales@climaxlube.com](mailto:sales@climaxlube.com)  
Climax Lubricants & Equipment Co. – U.S.A

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012  
713-923-2626 – Fax 713-928-9025 - [climaxlube@aol.com](mailto:climaxlube@aol.com)**