



## Climax Lubricants & Equipment Co.

### CLIMAX SPEC SHEET- #340 LUBRICANT/SEALANT

DROPPING POINT.....	NON -DROPPING
BASE OIL.....	SYNTHETIC
SHELF LIFE.....	5-YEARS (CONTOLED ENVIROMENT)
OXIDATION STABILITY.....	GOOD
TEMPERATURE RANGE.....	-20 DEG.F.TO +400 DEG.F.
PENETRATION (BULK).....	NLGI GRADE #3 (ASTM D-217 = 220-250)
(STICK).....	NLGI GRADE # 6 (ASTM D-217 = 85-115)
THICKENER.....	INORGANIC
COLOR.....	YELLOW
ADDITIVES.....	HYDROGEN SULFIDE SUPPRESSOR / OXIDATION & CORROSION INHIBITOR

NON TOXIC-HAZARDOUS MATERIAL  
FLASH POINT ABOVE 400 DEG.F.  
NON FLAMMABLE  
Manufactured in U.S.A. / Country of Origin – U.S.A.

This lubricant may be used where H2S and CO2 are encountered. The perfect lubricant for Sour Gases and Sour Crude Oils in Production, Pipelines and Refining.

Stephen D. Frauenberger, President – Sales/Manufacturing  
E-Mail: [sales@climaxlube.com](mailto:sales@climaxlube.com)  
Climax Lubricants & Equipment Co. – U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012  
713-923-2626 – Fax 713-928-9025 - [climaxlube@aol.com](mailto:climaxlube@aol.com)**