



## Climax Lubricants & Equipment Co.

### CLIMAX SPEC SHEET~ #400A LUBRICANT/SEALANT

DROPPING POINT.....	NON DROPPING
BASE OIL.....	PETROLEUM DERIVATIVE
SHELF LIFE.....	5-YEARS (CONTROLLED ENVIROMENTS)
OXIDATION STABILITY.....	GOOD
TEMPERATURE RANGE.....	-20 DEG.F.TO +450 DEG.F.
PENETRATION (BULK).....	NLGI GRADE #2 (ASTM D 217 = 265-295)
(STICK).....	NLGI GRADE # 6 (ASTM D 217 = 85-115)
THICKENER.....	RHEOLOGICAL ADDITIVE
COLOR.....	TAN

NON TOXIC-HAZARDOUS MATERIAL  
FLASH POINT ABOVE 400 DEG.F.  
NON FLAMMABLE  
Manufactured / Country of Origin – U.S.A.

This sealant has excellent tack and adhesion and offers very good resistance to Aqueous Solutions of Acids and Caustics: Alcohols, Alkalies, Ammonia(Gas or Liquid), Amines, Calcium Solutions, Fats, Glycerine, Glycols, Soap, Water & Gas, Black Liquor & Evaporates, Blast Furnace Gas, Cane Sugar, Cement, Coal Sludge, Coke Oven Gas, Distilled Water, Fertilizer Solutions, Helium, Hydrogen, Nitric Acid, Potash Solutions, Pulp Lines, Sewage, Slurries and Wood Pulp.

Stephen D. Frauenberger, President - Sales/Manufacturing  
Email: [sales@climaxlube.com](mailto:sales@climaxlube.com)  
Climax Lubricants & Equipment Co. - U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012  
713-923-2626 – Fax 713-928-9025 - [climaxlube@aol.com](mailto:climaxlube@aol.com)**