



# Climax Lubricants & Equipment Co.

## CLIMAX SPEC SHEET - #600 LUBRICANT/SEALANT

DROPPING POINT.....	NON-DROPPING
BASE OIL.....	SYNTHETIC
SHELF LIFE.....	5-YEARS (CONTROLLED ENVIROMENT)
OXIDATION STABILITY.....	GOOD
TEMPERATURE RANGE.....	-20 DEG.F.TO +500 DEG.F.
PENETRATION (BULK).....	NLGI GRADE #3 (ASTM D-217 = 220-250)
(STICK).....	NLGI GRADE #6 (ASTM D-217 = 85-115)
THICKENER.....	INORGANIC
COLOR.....	AMBER

NON TOXIC-HAZARDOUS MATERIAL  
FLASH POINT ABOVE 400 DEG.F.  
NON FLAMMABLE

This Valve Lubricant/Sealant is designed for General Hydrocarbon Service(Gas & Water Sealant) and is recommended for the following services: Aluminum Resinate or Sulfate, Aqueous Solutions, Butylene, Carbon Dioxide, Casien Paints, Cellulose Acetate, Cement Slurries, Coal Gas, Creosote, Drilling Mud, Gas-Dry, Nitrogen, Petrolatum, Salt Water Brine, Varnish, Vinyl Chloride and Water. Climax 600 can be used in Plug, Ball, & Gate Valves both as a Seat Sealant or body fill. Diesel resistant valve lubricant/sealant.

Stephen D. Frauenberger, President – Sales/Manufacturing  
E-Mail: [sales@climaxlube.com](mailto:sales@climaxlube.com)  
Climax Lubricants & Equipment Co. - U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012**  
**713-923-2626 – Fax 713-928-9025 - [climaxlube@aol.com](mailto:climaxlube@aol.com)**