



## Climax Lubricants & Equipment Co.

### CLIMAX SPEC SHEET~ #650 LUBRICANT/SEALANT

DROPPING POINT.....	NON-DROPPING
BASE OIL.....	SYNTHETIC
SHELF LIFE.....	5-YEARS (CONTROLLED ENVIROMENT)
OXIDATION STABILITY.....	GOOD
TEMPERATURE RANGE.....	-40 DEG.F.TO +500 DEG.F.
PENETRATION (BULK).....	NLGI GRADE #3 (ASTM D-217 = 220-250)
(STICK).....	NLGI GRADE # 6 (ASTM D-217 = 85-115)
THICKENER.....	INORGANIC
COLOR.....	BLUE

NON TOXIC-HAZARDOUS MATERIAL  
FLASH POINT ABOVE 400 DEG.F.  
NON FLAMMABLE  
Manufactured / Country of Origin – U.S.A.  
NOTE: Material has no restrictions for export to UAE.

A superior Plug Valve Lubricant / Sealant for Aliphatic Hydrocarbons and L.P.G. service suitable for kerosene, fuel oils, crude distillates, casing head gas, manufactured and natural gas, mineral oils and greases, light naphthas, ect. Unsuitable for aromatic solvents, strong acids and alkalies.

Stephen D. Frauenberger, President – Sales/Manufacturing  
Email: [sales@climaxlube.com](mailto:sales@climaxlube.com)  
Climax Lubricants & Equipment Co. – U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012  
713-923-2626 – Fax 713-928-9025 - [climaxlube@aol.com](mailto:climaxlube@aol.com)**