



Climax Lubricants & Equipment Co.

CLIMAX SPEC SHEET~ #66111 LUBRICANT/SEALANT

DROPPING POINT.....	NON-DROPPING
BASE OIL.....	POLYDIMETHYL SILOXANE FLUID
SHELF LIFE.....	INDEFINITE
OXIDATION STABILITY.....	EXCELLENT
TEMPERATURE RANGE.....	-50 DEG.F.TO +475 DEG.F.
PENETRATION (ASTM D-217).....	NLGI GRADE #3 (ASTM D-217= 220-250)
THICKENER.....	INORGANIC
COLOR.....	WHITE
SPECIFIC GRAVITY.....	1.03

NON TOXIC-HAZARDOUS MATERIAL
FLASH POINT ABOVE 400 DEG.F.
NON FLAMMABLE
Country of Origin/Manufacture – U.S.A.

PRODUCT DESCRIPTION:

Climax #66111 is a compound based on a inorganic-filled, high viscosity polydimethyl siloxane fluid. Climax #66111 is a stiff, high-tack dielectric compound which has been found useful in sealing and protecting electrical connections above and below ground. It's inherent water repellency provides dielectric protection for the lubrication of rubber and plastic components exposed to aqueous environments.

USES FOR CLIMAX #66111:

Automotive & Aircraft - Ignitions	Electrical Connectors
Rubber & Plastic Lubrication	Corrosion Protection
Moisture Barrier	"O"-Ring Lubricant
Stop Cock Lubricant	Valve Lubricant
High Vacuum Sealant	Thread Lubricant
Release Agent	Heat Transfer
Damping Applications	Underground Cable
Transformer Connectors	Connectors
Swivel Joints	

Stephen D. Frauenberger, President – Sales/Manufacturing
E-Mail: sales@climaxlube.com
Climax Lubricants & Equipment Co. - U.S.A.

P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012
713-923-2626 – Fax 713-928-9025 - climaxlube@aol.com