



Climax Lubricants & Equipment Co.

CLIMAX SPEC SHEET #666 LUBRICANT/SEALANT

DROPPING POINT.....	NON -DROPPING
BASE OIL.....	SYNTHETIC
SHELF LIFE.....	INDEFINITE
OXIDATION STABILITY.....	GOOD
TEMPERATURE RANGE.....	0 DEG.F.TO +300 DEG.F.
PENETRATION.....	NLGI GRADE #3 (ASTM 220-250)
THICKENER.....	HYDRATED SILICATE
FILLER.....	HYDROUS SILICATES
COLOR.....	BROWN

NON TOXIC-HAZARDOUS MATERIAL
FLASH POINT ABOVE 400 DEG.F.
NON FLAMMABLE
Manufactured/Country of Origin – U.S.A.

A medium temperature Hydrocarbon and Natural Gas lubricant/sealant particularly formulated for high pressure use in McEvoy Gate Valves (Seats) & General Type Slab Gate Valves that require enhanced sealing ability. Recommended for Natural Gas Pipelines,Refineries,Gasoline Plants and Wellhead Production.

Stephen D. Frauenberger, President – Sales/Manufacturing
E-Mail: sales@climaxlube.com
Climax Lubricants & Equipment Co. – U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012
713-923-2626 – Fax 713-928-9025 - climaxlube@aol.com**