



## Climax Lubricants & Equipment Co.

### CLIMAX SPEC SHEET- #711 LUBRICANT/SEALANT

DROPPING POINT.....	NON-DROPPING
BASE OIL.....	SYNTHETIC-POLYESTER
SHELF LIFE.....	5-YEARS (Controlled Environment)
OXIDATION STABILITY.....	EXCELLENT
TEMPERATURE RANGE.....	-40 DEG.F.TO +400 DEG.F.
PENETRATION (BULK).....	NLGI GRADE #3 (ASTM D-217 = 220-250)
(STICK).....	NLGI GRADE # 6 (ASTM D-217 = 85-115)
THICKENER.....	INORGANIC
COLOR.....	AMBER

NON TOXIC-HAZARDOUS MATERIAL  
FLASH POINT ABOVE 400 DEG.F.  
NON FLAMMABLE  
Manufactured / Country of Origin – U.S.A.

In addition to a general purpose sealant for liquid and gaseous aliphatic hydrocarbon service; (for example: wet or dry natural gas), this sealant has excellent resistance to internal combustion fuels: regular, premium and high octane gasolines- including oxygenated and reformulated fuels, jet fuels, aviation gasoline, diesel fuels, kerosene, fuel blending ingredients; such as alkylate and platform ate, fuel and lubricating oils, mixtures of these products and water in all proportions.

Stephen D. Frauenberger, President - Sales/Manufacturing  
Email: [sales@climaxlube.com](mailto:sales@climaxlube.com)  
Climax Lubricants & Equipment Co.-U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012  
713-923-2626 – Fax 713-928-9025 - [climaxlube@aol.com](mailto:climaxlube@aol.com)**