



Climax Lubricants & Equipment Co.

CLIMAX SPEC SHEET ~ #750 – STICK LUBRICANT/SEALANT

DROPPING POINT.....	NON-DROPPING
BASE OIL.....	SYNTHETIC
SHELF LIFE.....	5 YEARS (CONTROLLED ENVIROMENT)
OXIDATION STABILITY.....	GOOD
TEMPERATURE RANGE.....	0 DEG.F.TO +650 DEG.F.
PENETRATION.....	NLGI GRADE #6 (ASTM D-217, 85-115)
THICKNER.....	INORGANIC
FILLER.....	GRAPHITE, MOLYBDENUM-DISULFIDE
COLOR.....	BLACK

NON TOXIC-HAZARDOUS MATERIAL
FLASH POINT ABOVE 400 DEG.F.
NON FLAMMABLE

This lubricant exhibits high temperature and no-melt capabilities that take over in temperature ranges where other lubricants cease to be effective. The principle services include: Asphalt plants, Gas lifts, Hot oil, High temp.steam, Hot hydrocarbon gases / vapors, Salt water brine, Tars and Pitch.

Stephen D. Frauenberger, President - Sales/Manufacturing
Email: sales@climaxlube.com
Climax Lubricants & Equipment Co. – U.S.A

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012
713-923-2626 – Fax 713-928-9025 - climaxlube@aol.com**