



## Climax Lubricants & Equipment Co.

### CLIMAX SPEC SHEET~ 804-XH LUBRICANT/SEALANT

DROPPING POINT.....	NON-DROPPING
BASE OIL.....	SYNTHETIC
SHELF LIFE.....	INDEFINITE
OXIDATION STABILITY.....	GOOD
TEMPERATURE RANGE.....	-10 DEG.F.TO +400 DEG.F.
PENETRATION.....	NLGI GRADE #3 (ASTM 220-250)
THICKENER.....	INORGANIC
COLOR.....	AMBER

NON TOXIC-HAZARDOUS MATERIAL  
FLASH POINT ABOVE 400 DEG.F.  
NON FLAMMABLE  
Manufactured /Country of Origin – U.S.A.

This sealant has excellent resistance to Petroleum Products, Jet Fuels, Refinery and Petrochemical blends and Natural Gas. The material is suitable for use in Plug Valves, Ball Valves and API Gate Valves; both as a body fill and seat sealant.

Stephen D. Frauenberger, President - Sales/Manufacturing  
E-Mail: [sales@climaxlube.com](mailto:sales@climaxlube.com)  
Climax Lubricants & Equipment Co. - U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012  
713-923-2626 – Fax 713-928-9025 - [climaxlube@aol.com](mailto:climaxlube@aol.com)**