



Climax Lubricants & Equipment Co.

CLIMAX SPEC SHEET ~ #900-T LUBRICANT/SEALANT

DROPPING POINT.....	NON-DROPPING
BASE OIL.....	SYNTHETIC
SHELF LIFE.....	INDEFINITE
OXIDATION STABILITY.....	GOOD
TEMPERATURE RANGE.....	-20 DEG.F.TO +650 DEG.F.
PENETRATION.....	NLGI GRADE #3
THICKENER.....	INORGANIC
FILLER.....	MOLYBDENUM-DISULFIDE TEFLON
COLOR.....	BLACK

NON TOXIC-HAZARDOUS MATERIAL
FLASH POINT ABOVE 400 DEG.F.
NON FLAMMABLE

An all purpose High Temperature Hydrocarbon and Natural Gas lubricant. Recommended for Natural Gas Pipelines, Refineries, Gasoline Plants, Petrochemical Plants, Rubber Plants, Compressor Discharge Valves, Dehydrator Valves, Steel Mills and Tailing Systems. The material is suitable for use in Plug Valves, Ball Valves and API Gate Valves; both as a body fill and seat sealant. Climax 900-T contains 20% virgin Teflon for badly Scored or Worn Plug and Ball Valves.

Stephen D. Frauenberger, President – Sales/Manufacturing
Email: sales@climaxlube.com
Climax Lubricants & Equipment Co. – U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012
713-923-2626 – Fax 713-928-9025 - climaxlube@aol.com**