



Climax Lubricants & Equipment Co.

CLIMAX SPEC SHEET~ #901 LUBRICANT/SEALANT

DROPPING POINT.....	NON -DROPPING
BASE OIL.....	SYNTHETIC, SILICONE
SHELF LIFE.....	5 YEARS (CONTROLLED ENVIROMENT)
OXIDATION STABILITY.....	GOOD
TEMPERATURE RANGE.....	-40 DEG.F.TO +300 DEG.F.
PENETRATION (BULK).....	NLGI GRADE #3 (ASTM 220-250)
(STICK).....	NLGI GRADE # 6 (ASTM 85-115)
THICKENER.....	INORGANIC
FILLER.....	MOLYBDENUM DISULFIDE
COLOR.....	BLACK

NON TOXIC-HAZARDOUS MATERIAL
FLASH POINT ABOVE 400 DEG.F.
NON FLAMMABLE
Manufactured / Country of Origin – U.S.A.

Frosty 901 is Climax`s cold weather 900 Lubricant. Climax 900 starts stiffening up at temperatures around 20 DEG.F and below; although 900 is serviceable to 0 DEG.F. This Valve Lubricant was developed for parts of the country where temperatures of 20 DEG.F and below are sustained for long periods of time. Frosty 901 Valve Lubricant is recommended for General Hydrocarbon Service; including Natural Gas Pipelines, Compressor Stations, Gasoline Plants, Production Fields, Christmas Trees, Hydrogen Sulfide and Mercaptans. Frosty 901 will not start "Thinning Out" in spring temperatures, when 900 is again recommended for general services.

Stephen D. Frauenberger, President – Sales/Manufacturing
E-mail: sales@climaxlube.com
Climax Lubricants & Equipment Co. – U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012
713-923-2626 – Fax 713-928-9025 - climaxlube@aol.com**