



## Climax Lubricants & Equipment Co.

### CLIMAX SPEC SHEET - #950 LUBRICANT/SEALANT

DROPPING POINT.....	NON-DROPPING
BASE OIL.....	SYNTHETIC
SHELF LIFE.....	5-YEARS (Controlled Environment)
OXIDATION STABILITY.....	GOOD
TEMPERATURE RANGE.....	-20 DEG.F.TO +450 DEG.F.
PENETRATION.....	NLGI GRADE #3 (ASTM 220-250)
THICKENER.....	INORGANIC
COLOR.....	AMBER

NON TOXIC-HAZARDOUS MATERIAL  
FLASH POINT ABOVE 400 DEG.F.  
NON FLAMMABLE  
Manufactured/Country of Origin – U.S.A.

In addition to excellent service as a general purpose sealant for liquid and gaseous aliphatic hydrocarbons, this sealant has excellent resistance to internal combustion fuels, gasolines, jet fuels, refinery and petrochemical blends, propylenes, benzenes, toluenes, butadienes, xylenes, styrenes, cumenes and other LPG`S.

Stephen D. Frauenberger, President - Sales/Manufacturing  
E-Mail: [sales@climaxlube.com](mailto:sales@climaxlube.com)  
Climax Lubricants & Equipment Co.-U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012  
713-923-2626 – Fax 713-928-9025 - [climaxlube@aol.com](mailto:climaxlube@aol.com)**