



Climax Lubricants & Equipment Co.

CLIMAX SPEC SHEET~ GY-600 LUBRICANT/SEALANT

DROPPING POINT.....	NON -DROPPING
BASE OIL.....	SYNTHETIC
SHELF LIFE.....	INDEFINITE
OXIDATION STABILITY.....	GOOD
TEMPERATURE RANGE.....	-20 DEG.F.TO +300 DEG.F.
PENETRATION.....	NLGI GRADE #3 (ASTM 220-250)
THICKENER.....	INORGANIC
COLOR.....	AMBER
ADDITIVES.....	HYDROGEN SULFIDE SUPPRESSOR/ OXIDATION & CORROSION INHIBITOR
NON TOXIC-HAZARDOUS MATERIAL	
FLASH POINT ABOVE 400 DEG.F.	
NON FLAMMABLE	
Manufacturer/Country of Origin – U.S.A.	

This sealant has excellent resistance to Petroleum Products, Jet Fuels, Refinery and Petrochemical blends and Natural Gas. The material is suitable for use in Plug Valves, Ball Valves and API Gate Valves; both as a body fill and seat sealant. Diesel Resistant Valve Lubricant/Sealant.

Stephen D. Frauenberger, President - Sales/Manufacturing
Email: sales@climaxlube.com
Climax Lubricants & Equipment Company – U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012
713-923-2626 – Fax 713-928-9025 - climaxlube@aol.com**