



Climax Lubricants & Equipment Co.

CLIMAX SPEC SHEET~ POLYSEAL #3 LUBRICANT/SEALANT

DROPPING POINT.....	NON-DROPPING
BASE OIL.....	SYNTHETIC-POLYMERIZED HYDROCARBON DERIVATIVE
SHELF LIFE.....	INDEFINITE
OXIDATION STABILITY.....	GOOD
TEMPERATURE RANGE.....	32 DEG.F.TO + 650 DEG.F.
PENETRATION (BULK).....	NLGI GRADE #3.5 (ASTM 190-230)
(STICK).....	NLGI GRADE # 6 (ASTM 85-115)
THICKENER.....	METALLIC-SOAP
FILLER.....	HYDROUS SILICATE
COLOR.....	RED

NON TOXIC-HAZARDOUS MATERIAL
FLASH POINT ABOVE 400 DEG.F.
NON FLAMMABLE
Manufactured/Country of Origin – U.S.A.

Climax Polyseal #3 Valve Lubricant/Sealant is designed for Super-Heated Steam & Water Service. This Lubricant/Sealant is manufactured from a high molecular weight petroleum derivative Hydrocarbon Polymer and Exhibits excellent resistance, temperature stability and high metal adhesion in water solutions.
NOTE: Climax Polyseal #3 comes in bulk/stick form and can be used in jack screw applications (Has a Putty-Like Consistency).

Stephen D. Frauenberger, President - Sales/Manufacturing
Email: climaxlube@aol.com
Climax Lubricants & Equipment Co. – U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012
713-923-2626 – Fax 713-928-9025 - climaxlube@aol.com**