



## Climax Lubricants & Equipment Co.

### CLIMAX SPEC SHEET-STANDARD PAC-EZ VALVE STEM PACKING

DROPPING POINT.....	NON -DROPPING
BASE OIL.....	SYNTHETIC
SHELF LIFE.....	INDEFINITE
OXIDATION STABILITY.....	GOOD
TEMPERATURE RANGE.....	-20 DEG.F.TO +500 DEG.F.
PENETRATION.....	N/A
THICKENER.....	INORGANIC RHEOLOGICAL ADDITIVE
FILLER.....	TEFLON, CEDAR FIBER, MILLED FIBER
COLOR.....	BLUE

NON TOXIC-HAZARDOUS MATERIAL  
FLASH POINT ABOVE 400 DEG.F.  
NON FLAMMABLE  
Manufactured/ Country of Origin – U.S.A.

Climax Standard Pac-Ez is used for API Gate Valve Stems, Rockwell Hyperseals, Orbit Ball Valves, Ect.  
Recommended for Hydrocarbon & L.P.G. Service.

Stephen D. Frauenberger, President - Sales/Manufacturing  
Email: [sales@climaxlube.com](mailto:sales@climaxlube.com)  
Climax Lubricants & Equipment Co. – U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012  
713-923-2626 – Fax 713-928-9025 - [climaxlube@aol.com](mailto:climaxlube@aol.com)**