



Climax Lubricants & Equipment Co.

CLIMAX SPEC SHEET ~ VCS #1

DROPPING POINT.....	NON DROPPING
BASE OIL.....	SYNTHETIC
SHELF LIFE.....	5 -YEARS
OXIDATION STABILITY.....	GOOD
TEMPERATURE RANGE.....	-30 DEG.F. TO +500 DEG.F.
PENETRATION.....	N/A
THICKENER.....	N/A
FILLER.....	N/A
COLOR.....	AMBER

NON TOXIC-HAZARDOUS MATERIAL(DOES NOT CONTAIN OZONE DEPLETING SUBSTANCE)

FLASH POINT ABOVE 400 DEG.F.

NON FLAMMABLE

Manufactured/Country of Origin – U.S.A.

VALVE CLEANER/FLUSH (LIQUID FORM)

Climax`s VCS is formulated from base oils of low viscosity which have been used in the formulation of most valve lubricants and sealants.

Climax`s VCS will dissolve or soften the hardened or dried lubricants, lacquer and residual gum deposits in a valve which will make it hard to operate.

This product is not a lubricant or sealant, and is compatible with other sealants and lubricants.

Use as much of this product as the valve will take, then wait 20 minutes and try to operate the valve. If the valve will turn, work it back and forth to make sure the product can get into all the passages and around the plug. If after first application the valve will not turn, wait 20 minutes, then repeat the application. After procedure is completed a recommended valve lubricant/sealant should follow.

Climax VCS is available in 8oz. and one quart poly bottles, one gallon paint (friction) top cans, 5 qt.(10-lb) cans and 5or 6 gallon (40 lbs) pails.

Stephen D. Frauenberger, President - Sales/Manufacturing

Email: sales@climaxlube.com

Climax Lubricants & Equipment Co. – U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012
713-923-2626 – Fax 713-928-9025 - climaxlube@aol.com**