



Climax Lubricants & Equipment Co.

CLIMAX SPEC SHEET ~ VCS #2G

DROPPING POINT.....	NON DROPPING
BASE OIL.....	SYNTHETIC, ALCOHOL
SHELF LIFE.....	INDEFINITE
OXIDATION STABILITY.....	GOOD
TEMPERATURE RANGE.....	-30 DEG.F. TO +250 DEG.F.
PENETRATION.....	N/A
THICKENER.....	INORGANIC
FILLER.....	MOLYBDENUM DISULFIDE
COLOR.....	BLACK
NON TOXIC-HAZARDOUS MATERIAL(DOES NOT CONTAIN OZONE DEPLETING SUBSTANCE)	
FLASH POINT ABOVE 250 DEG.F.	
NON FLAMMABLE	
Manufactured/Country of Origin – U.S.A.	

VALVE CLEANER & SOLVENT (GELLED FORMULA)

Climax`s VCS #2G is formulated from base oils of low viscosity which have been used in the formulation of most valve lubricants and sealants; Also contains alcohol and moly for faster and more efficient operation.

Climax`s VCS #2G will dissolve or soften the hardened or dried lubricants, lacquer and residual gum deposits in a valve which will make it hard to operate.

This product is not a lubricant or sealant, and is compatible with other sealants and lubricants.

Use as much of this product as the valve will take, then wait 20 minutes and try to operate the valve. If the valve will turn, work it back and forth to make sure the product can get into all the passages and around the plug. If after first application the valve will not turn, wait 20 minutes, then repeat the application. After procedure is completed a recommended valve lubricant/sealant should follow.

Climax VCS #2G is available in 14-1/2 oz. grease gun cartridges, 5 qt.(10-lb) cans and 5 or 6 gallon(40 lbs) pails. Note: This material comes in liquid form as well.

Stephen D. Frauenberger, President - Sales/Manufacturing

Email: sales@climaxlube.com

Climax Lubricants & Equipment Co. – U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012
713-923-2626 – Fax 713-928-9025 - climaxlube@aol.com**