



## Climax Lubricants & Equipment Co.

### CLIMAX SPEC SHEET ON VALVE TURN #2 LUBRICANT

|                          |                                                                           |
|--------------------------|---------------------------------------------------------------------------|
| DROPPING POINT.....      | NON DROPPING                                                              |
| BASE OIL.....            | PETROLEUM DERIVATIVE,<br>SYNTHETIC-POLYEMERIZED<br>HYDROCARBON DERIVATIVE |
| SHELF LIFE.....          | INDEFINITE                                                                |
| OXIDATION STABILITY..... | GOOD                                                                      |
| TEMPERATURE RANGE.....   | -20 DEG.F.TO +500 DEG.F.                                                  |
| PENETRATION.....         | NLGI GRADE #2.5                                                           |
| THICKENER.....           | RHEOLOGICAL ADDITIVE                                                      |
| FILLER.....              | MOLYBDENUM-DISULFIDE                                                      |
| COLOR.....               | BLACK                                                                     |

NON TOXIC-HAZARDOUS MATERIAL  
FLASH POINT ABOVE 400 DEG.F.  
NON FLAMMABLE

Valve Turn #2 is designed for Hard To Operate Valves and to Work out Valve Residues left in Plug Valves. VT #2 is resistant to Acids and Caustics. When desired or original torque is achieved an appropriate valve lubricant /sealant should be injected to replace the VT#2 according to line product, temperature gradient and type(condition) of valve etc.

Stephen D. Frauenberger, President – Sales/Manufacturing  
Email: [sales@climaxlube.com](mailto:sales@climaxlube.com)  
Climax Lubricants & Equipment Company

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012  
713-923-2626 – Fax 713-928-9025 - [climaxlube@aol.com](mailto:climaxlube@aol.com)**