



Climax Lubricants & Equipment Co.

CLIMAX SPEC SHEET~ #333-10 PAC-EZ

DROPPING POINT.....	NON-DROPPING
BASE OIL.....	SYNTHETIC-POLYMERIZED HYDROCARBON DERIVATIVE
SHELF LIFE.....	INDEFINITE
OXIDATION STABILITY.....	GOOD
TEMPERATURE RANGE.....	32 DEG.F.TO +750 DEG.F.
PENETRATION.....	N/A
THICKENER.....	METALLIC-SOAP
FILLER.....	GRAPHITE-KEVLAR
COLOR.....	BLACK

NON TOXIC-HAZARDOUS MATERIAL
FLASH POINT ABOVE 400 DEG.F.
NON FLAMMABLE
Manufactured/Country of Origin – U.S.A.

A special designed graphite-kevlar impregnated packing for Hi-Pressure and Hi-Temp steam expansion joints. Climax 333-10 can also be used to pack off casing wellheads (Oil & Gas Production) to prevent a combination of pressures and materials between the casing head and tubing (referred to as the annulus) from escaping into the atmosphere. Also recommended as a valve stem packing for temperatures exceeding 500 DEG.F. Principle services include geothermal and hot aliphatic hydrocarbon liquids, gases and vapors.

Stephen D. Frauenberger, President – Sales/Manufacturing
Email: sales@climaxlube.com
Climax Lubricants & Equipment Co. – U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012
713-923-2626 – Fax 713-928-9025 - climaxlube@aol.com**